

Manual call points

Order-No. MCP-R-01



Manual Call Point (new design)

- conventional to be interfaced with SDI933 or SCI933
- NO or NC contact
- Glass break. Resettable version available. Specify into order
- Standard: EN54-11
- Technical specification:
 - maximum voltage: 30VDC
 - current rating: 2A
 - cable termination: 0.5-2.5mm²
 - humidity: 0-95% non condensing
 - operating temperature: -10°C to 55°C
 - storage temperature: -10°C to 55°C
 - IP rating: IP24D, plain hinged cover included
 - colour-material: Red RAL3001-PC/ABS
 - dimensions: 89x93x60mm
 - weight: 160g (surface mount), flush mount available

LPCB certificate, VdS pending

Order-No. MCP-R-01L

Manual Call Point (new design)

- Same as MCP-R-01 with latching LED indication

Order-No. MCP-Y11

Manual Call Point (new design)

- Same as MCP-R-01 colour Yellow

Order-No. MCP-G12

Manual Call Point (new design)

- Same as MCP-R-01 colour Green

Order-No. WR4001



Manual Call Point, waterproof, IP67

- conventional to be interfaced with SDI933 or SCI933
- NO or NC contact
- Glass break.
- Standard: EN54-11
- Technical specification:
 - maximum voltage: 30VDC or 240VAC
 - current rating: 5A
 - operating temperature: -30°C to 70°C
 - IP rating: IP67, waterproof
 - colour: red RAL3001

LPCB certificate

Order-No. 2470 U



Manual Call Point, IP54

- conventional to be interfaced with SDI933 or SCI933
- clear cover protection
- plastic break glass.
- Technical specification:
 - maximum voltage: 75VDC
 - maximum current: 3A
 - operating temperature: -10°C to 50°C
 - IP rating: IP54
 - colour: red
 - material: thermoplastic
 - weight: 180g

Order-No. 2470P U**Manual Call Point, IP54**

- Same as 2470 U with Reset option



Order-No. 3470**Manual Call Point, Low profile**

- conventional to be interfaced with SDI933 or SCI933
- only 30mm deep
- break glass.
- NO or NC contact.
- Technical specification:
 - maximum voltage: 75VDC
 - maximum current: 3A
 - operating temperature: -10°C to 50°C
 - IP rating: IP30
 - colour: red
 - material: thermoplastic
 - weight: 130g



Order-No. 2472 U**Spare Glass**

- Universal spare glass for 2470

Photograph not available

Order-No. 1472 U**Spare Glass**

- Universal spare glasses for manual call point model 1469, 1470, 2493, 3470, 3480 (10 pcs)

Photograph not available


Order-No. KG**Spare Glass**

Replacement glass for FT 513, label according to EN-54

Photograph not available

Addressable Manual Call Points

Order-No. MCP633-ALU



Manual Call Point ALU

- loop detector in ALU-housing
 - automatic addressing (soft-addressing)
 - red LED for Alarm
 - intelligent function monitoring of button mechanism
 - Technical specification:
 - Type of connection: 2-wire bus
 - Addressing: 126 elements per loop
 - Operating voltage: 15-30 VDC
 - Standby current: 250 μ A
 - Alarm current: 5 mA
 - Operating temperature: -20°C to +70°C
 - Class of protection: IP42
- Dimensions: 125 x 125 X 34 mm
Colour: red, RAL 3000
VdS approval No.: G 206013

Order-No. MCP633-ABS



Manual Call Point ABS

- loop detector in ABS-housing
 - automatic addressing (soft-addressing)
 - red LED for Alarm
 - intelligent function monitoring of button mechanism
 - Technical specification:
 - Type of connection: 2-wire bus
 - Addressing: 126 elements per loop
 - Operating voltage: 15-30 VDC
 - Standby current: 250 μ A
 - Alarm current: 5 mA
 - Operating temperature: -10°C to +60°C
 - Class of protection: IP42
- Dimensions: 125 x 125 X 34 mm
Colour: red, RAL 3000
VdS approval No.: G 206013

Fittich S.A.